



- 1-Water draining gutter
- 2-Polyurethane insulating wedge
- 3-Tile supporting profile
- 4-XDP FAKRO vapour permeable collar
- 5-Tress made of sheep wool FAKRO (XDP)
- 6-Blocks made of sheep wool FAKRO (XDP)
- 8-XLIV internal lining horizontal element FAKRO
- 17-Kalor
- 33-Installation bracket
- 109-XDS air-tight flashing
- 166-Top ruing and pivot window
- FPP-V U3, FPU-V U3 preSelect FAKRO
- 174-EHN flashing side element FAKRO
- 175-EHN flashing lower element FAKRO

Warning! The present drawing is for informational-demonstrative purposes only and as such cannot constitute a basis for performance. All dimensions presented in this drawing should be verified on site. Because of the fact that the drawing is a schematic one, FAKRO shall not assume any responsibility for the actual installation quality on the roof. This drawing is FAKRO's property and cannot be published or used publicly without our written consent.

FPF-V U3 preSelect FPU-V U3 preSelect	EHN	TILE	XLIV	15° - 55°
Vertical and horizontal cross-section: FPF-V U3, FPU-V U3 preSelect roof window with EHN flashing for high-profiled roofing materials	FORMAT: A4	SCALE: 1:10/1:5	DATE: 06.2011	

  

FPF-V U3, FPU-V U3 preSelect	Frame width [Stimm]	Frame height [Himm]	Window symbol
547	980	980	02
	1180	1180	16
	980	980	03
657	1180	1180	04
	980	980	05
	1180	1180	06
777	1400	1400	07
	1600	1600	13
	980	980	15
	1180	1180	08
	1400	1400	09
937	1600	1600	80*
	980	980	20
1137	1180	1180	10
	1400	1400	11
	980	980	12
1337	1180	1180	18**
	1400	1400	17*

\*- with roller shutter ARZ - 35-55°  
\*\*-only without roller shutter ARZ